




CN-2V 800AH Lead acid battery



Technology data

Rated voltage	Capacity (10hr,1.80V/Cell)	Weight	Max discharge current	Max charging current	Self-discharge (25°C)	Recommended Using temperature	Cover Material
2V	800Ah	46Kg	30I ₁₀ A(3min)	≤0.25C ₁₀	≤3%/month	15°C~25°C	ABS
Using temperature	Charging Voltage (25°C)	Charging Mode (25°C)		Cycle life		Capacity Affected by Temperature	
Discharge: -45°C~50°C	floating charge:	Float Charge: 2.275±0.025V		100%DOD 572 times		105% @ 40°C	
Charge: -20°C~45°C	2.25V-2.3V	Temperature parameters: ±3mV/°C		50%DOD 1422 times		90% @ 0°C	
Storage: -30°C~40°C	equalizing charge:	Cycle Charge: 2.45±0.05V		30%DOD 2218 times		70% @ -20°C	
	2.35V-2.4V	Temperature Compensation Coefficient ±5mV/°C					

Features

battery, Maintenance free and easy to use,Contemporary advanced technology research and development of new high-performance batteries,It can be widely used in solar energy , wind energy, telecommunication systems, off-grid systems, UPS and other fields. The designed life for the battery could be eight years up for float use.

Different discharge time at different terminal Voltage, discharge time(Amps,25)

F.V/Time	5min	10min	15min	30min	45min	1h	2h	3h	4h	5h	8h	10h
1.60V	1374	1164	1099	840	637	512	309	226	182	153	105	86.7
1.65V	1212	1068	1034	776	610	488	301	221	178	150	104	85.4
1.70V	1164	1008	986	711	571	461	290	214	174	148	102	84.2
1.75V	1109	956	934	663	546	443	280	208	170	144	101	82.2
1.80V	1067	907	881	630	507	414	267	202	163	141	98.0	80.0
1.85V	944	804	781	570	459	374	242	190	156	134	95.0	77.6

Certificate

ISO9001

CE

Compliant standards:

GB/T 22473-2008

GB/T 19638.2-2005

YD/T799-2002

IEC61427-2005

GB/T 19001-2016 idt ISO 9001:2015

EN IEC 61000-6-2:2019,EN IEC 61000-6-4:2019

EN IEC 61000-3-2:2019+AI:2021


EN 61000-3-3:2013+AI:2019




Performance characteristics

NOTE: The above data are average values, and can be obtained within 3 charge/discharge cycles. These are not minimum values. Cell and battery designs/specifications are subject to modification without notice.


Charge Characteristic




Discharge Characteristic (20°C)




Temperature vs Float Life



Self Discharge Characteristics



Cycle Life vs Depth of Discharge



Capacity vs Temperature

